



RECOMMENDBD P.C.B PATTBRN LAY OUT

NOTE:

1.MATERIAL:

- a.HOUSING:PBT GLASS FIBRE PBT
- b.CONTACT:PHOSPHOR BRONZE T=0.25mm (SURFACE PLATING:AU1u"+Sn100u"+Ni60u")
- c.SHEEL:BRASS T=0.30mm (SURFACE PLATING:Ni100u"~120u")

2.ELECTRIC:

- g.CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c.DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
- d.OPERATING TEMPERATURE: -55??- 105??

深圳市金航标电子有限公司

WWW.BDS666.COM

KH-2AF90ZJ-17.5JB

0755-83044319

UNLESS OTHERWISE SPECIFIED TOLERANCE

.X	±0.20
.XX	±0.15
.XXX	±0.10
ANG.	±2°

DRAWN

H.Q.huocuy

APPROVED

DATE

2011.03.18



UNIT

MM

SCALE

3/1

SIZE

A4

TITLE USB AF 双层半包有后盖平弹直脚

PART NO.

DOC. NO.

REV.

A