



1. Material:
  - Contact: Phosphor Bronze
  - Insulator: PBT+30%
  - G. F. UL 94V-0
  - Shell: SPCC
2. Mechanical:
  - Mating: 35N max.
  - Withdrawal Force: 10N min.
  - Durability: 1500 cycles min.
3. Electrical:
  - Current-max (amps) 1.5A
  - Voltage-max (volts) 30V
  - Withstanding Voltage 750V AC
  - Contact Resistance (ohms) 30 milliohms max insulation
  - Resistance (ohms) 1000 Megohms min.
4. Plating:
  - Contacts: Gold And Tin Over Nickel Plated
  - Shell: Nickel over all plating.
5. Environmental:
  - Temperature Range: -55 to 85 .

<b>产品图</b> MANUFACTURING FIG	<b>公差一览表</b> TOLERANCE UNLESS OTHERWISE		深圳市金航标电子有限公司	WWW.BDS666.COM
			KH-2AF180-10JB	0755-83044319
	<b>单位</b> UNIT	<b>MM</b>	<b>INCH</b>	<b>产品名称</b> USB A/F 双层直插10.0毫米无脚
	.X	±0.20	.X	±—
	.XX	±0.10	.XX	±—
	.XXX	±0.05	.XXX	±—
	2013.08.29			<b>角法</b> YES
	<b>比例</b> SCALE	1:1	<b>制图</b> DRAWING	<b>审核</b> CHECK
	<b>版本</b> REV	A1	<b>设计</b> DESIGN	<b>核准</b> APPD
			<b>图号</b>	<b>CDC1</b>